

**Connection requirements:**

Water quality: drinking water quality

Water pressure: 200 to 500 kPa (2.0 to 5.0 bar)

Water hardness: 50-80 mg CaO/l water (5-8° dH, 9-15° fH)

Chlorine content: Max. 50 mg/l

Ideal pH value: 7.0

Waste water connection with siphon: Geberit 50 mm

If a filter is used, it needs to be changed at least once a year.

x = standard equipment, incomplete fields = configuration not possible

**VISTA****50202**

<b>STANDARD EQUIPMENT/DESIGN</b>	<b>50202</b>
Beverages per hour	350
Max. beverage dispensing <b>SIMULTANEOUSLY!!</b>	3
Separate hot water dispensing	X
Steam lance X	X
Multitouch for 3 different coffee strengths per product	X
Coffee dispenser height (mm)	65 - 175
Number of possible beverages	24
Premium high-performance grinder with 64 mm special steel discs - grinding time from 1.5 sec.	X
Simultaneous operation: Simultaneous dispensing of all beverages set (tea, 2x coffee, chocolate and steam)	X
Milk pump speed regulated MPS	X
Opti Clean (automatic milk system rinsing) OC	X
Tech. data - waste water connection: Geberit 50 mm	X
Tech. data - colour: Black - powder coated with LED	X
Techn. data - weight: (kg)	75
Techn. data - dimensions: Width (mm)	380
Techn. data - dimensions: Height without bean or chocolate container (mm)	685
Techn. data - dimensions: Height with bean or chocolate container (mm)	880
Techn. data - dimensions: Depth (mm)	600
Techn. data - water connection: Fixed water connection min. 2 bar	X
Techn. data - boiler: Boiler contents	3 litres
Techn. data: Power (W)	4600
Techn. data: Current (V)	380 - 415